

Package ‘polyhedralCubature’

November 22, 2023

Title Multiple Integration over Convex Polyhedra

Version 1.1.0

Description Evaluation of multiple integrals over convex polyhedra. This is useful when the bounds of the integrals are some linear combinations of the variables.

License GPL-3

URL <https://github.com/stla/polyhedralCubature>

BugReports <https://github.com/stla/polyhedralCubature/issues>

Imports gmp, magrittr, Matrix, ompr, qspray, rccd, SimplicialCubature, spray, tessellation

Encoding UTF-8

RoxygenNote 7.2.3

Suggests knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Author Stéphane Laurent [aut, cre]

Maintainer Stéphane Laurent <laurent_step@outlook.fr>

Repository CRAN

Date/Publication 2023-11-22 17:00:02 UTC

R topics documented:

| | |
|-----------------------------------|----------|
| getAb | 2 |
| integrateOverPolyhedron | 2 |
| pipe-operator | 3 |
| Index | 4 |

`getAb`*Easily get the matrix A and the vector b*

Description

Get the matrix A and the vector b representing the linear inequalities with a user-friendly syntax.

Usage

```
getAb(model)
```

Arguments

`model` a "MIP model"; see the example

Value

A list with the matrix A and the vector b for usage in [integrateOverPolyhedron](#).

Examples

```
library(ompr)
model <- MIPModel() %>%
  add_variable(x) %>% add_variable(y) %>% add_variable(z) %>%
  add_constraint(-5 <= x) %>% add_constraint(x <= 4) %>%
  add_constraint(-5 <= y) %>% add_constraint(y <= 3 - x) %>%
  add_constraint(-10 <= z) %>% add_constraint(z <= 6 - x - y)
getAb(model)
```

`integrateOverPolyhedron`*Multiple integral over a polyhedron*

Description

Multiple integral over a convex polyhedron given by a set of linear inequalities. See the vignette for explanations and examples.

Usage

```
integrateOverPolyhedron(f, A, b)
```

Arguments

| | |
|------|--|
| f | either a function, a spray polynomial, or a qspray polynomial; its number of variables must match the number of columns of the matrix A |
| A, b | matrix and vector defining the linear inequalities which must be in numeric mode or, for exactness, in character mode, with an integer or a fraction as each entry; if f is a qspray polynomial, then A and b will be converted to character mode if they are in numeric mode, with the function <code>d2q</code> |

Value

There are three possible values: an output of `adaptIntegrateSimplex` if f is a function, an output of `integrateSimplexPolynomial` if f is a **spray** polynomial, or a character representing the value of the integral as a fraction if f is a **qspray** polynomial.

Examples

```
A <- rbind(
  c(-1, 0, 0), # -x
  c( 1, 0, 0), # x
  c( 0,-1, 0), # -y
  c( 1, 1, 0), # x+y
  c( 0, 0,-1), # -z
  c( 1, 1, 1) # x+y+z
)
b <- c(
  5, 4, # -5 < x < 4      <=> -x < 5 & x < 4
  5, 3, # -5 < y < 3-x    <=> -y < 5 & x+y < 3
  10, 6 # -10 < z < 6-x-y <=> -z < 10 & x+y+z < 6
)
f <- function(x, y, z) {
  x*y + 5*cos(z)
}
integrateOverPolyhedron(f, A, b)
```

 pipe-operator

Pipe operator

Description

This is the 'magrittr' pipe operator. We import it in this package in order to help the user to construct the `model` argument of the `getAb` function.

Index

`%>%` (pipe-operator), [3](#)

`adaptIntegrateSimplex`, [3](#)

`d2q`, [3](#)

`getAb`, [2](#), [3](#)

`integrateOverPolyhedron`, [2](#), [2](#)

`integrateSimplexPolynomial`, [3](#)

pipe-operator, [3](#)