

lavaanExtra: Convenience Functions for Package *lavaan*

Rémi Thériault ¹

¹ Department of Psychology, Université du Québec à Montréal, Québec, Canada

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Open Journals](#) 

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

lavaanExtra is an R package that offers an alternative and vector-based syntax to the package *lavaan*, as well as other convenience functions such as naming paths and defining indirect effects automatically. It also offers convenience formatting optimized for publication and script sharing workflows.

Statement of need

lavaan (Rosseel, 2012) is a very popular R package for structural equation modeling (SEM). The package relies on specific operators to define latent variables, regressions, covariances, indirect effects, and so on. However, some individuals (e.g., beginners to R and *lavaan*)—or in some cases power users—may prefer not having to specify the operators themselves, or would like to see some steps automatized, such as generating the *lavaan* model layout or defining indirect effects. Furthermore, for researchers, it can be relatively difficult to extract relevant statistical outputs in the form of tables and figures that are suitable for scientific publication.

lavaanExtra does mainly two things to address these issues. First, it offers an alternative, code-efficient flexible modular syntax that allows automatizing certain steps, such as defining indirect effects in certain scenarios or the desired structure of a SEM model to be plotted (however, note that *lavaan* is also compatible with a modular approach). Second, it facilitates the analysis-to-publication workflow by providing publication-ready tables and figures following the style requirements of the American Psychological Association (APA).

Usage

There is a single function at the center of the proposed alternative syntax, `write_lavaan()`. The idea behind `write_lavaan()` is to define individual components (regressions, covariances, latent variables, etc.), provide them to the function, and have it write the *lavaan* model, so the user does not have to worry about making typos in the specific symbols required for each aspect of the model.

There are several benefits to this approach. Some *lavaan* models can become very large. By defining the entire model every time, such as is typical with *lavaan* users, not only do we break the DRY (Don't Repeat Yourself) principle, but our scripts can also become long and unwieldy. This problem gets worse in the scenario where we want to compare several variations of the same general model. `write_lavaan()` allows the user to reuse code components, say, only the latent variables, for future models.

This aspect also allows better control over the user's code. If the user makes a mistake in one of, say, five SEM models definition, the user will have to change it at all five places within the script. With `write_lavaan()`, users only need to define the reusable component the first time, or until they need to change that component again.

40 The vector-based approach also allows the use of functions to define components. For example,
41 if all scale items are named consistently, say x1 to x50, one can use `paste0("x", 1:50)`
42 instead of typing all the items by hand and risk making mistakes. However, note that reusable
43 components through functions is also compatible with lavaan.

44 Another issue with lavaan models is the readability of the code defining the model. One can
45 go to lengths to make it pretty, but not everyone does, and many people do not use the same
46 strategies to organize the information of the model definition. With `write_lavaan()`, not
47 only is the model information standardized, but it is also neatly divided into clear and useful
48 categories.

49 Finally, for beginners, it can be difficult to remember the correct lavaan symbols for each
50 specific operation. `write_lavaan()` uses familiar names to convert the information to the
51 correct symbols. Even for people familiar with lavaan syntax, this approach can save time.
52 The function also offers the possibility to define the named paths automatically with clear and
53 intuitive names.

54 I provide a simple Confirmatory Factor Analysis (CFA) example below using the
55 `HolzingerSwineford1939` dataset (Holzinger & Swineford, 1939). The dataset con-
56 tains the mental ability test scores of children. In this example, we want to define the latent
57 variables `visual` (visual perception ability), `textual` (reading and writing ability), and `speed`
58 (processing speed ability), which are defined by items 1 to 9, respectively. We can then use
59 the `cat()` function on the resulting object (of type character) to read it in the traditional way
60 and make sure we have not made any mistake.

```
library(lavaanExtra)

x <- paste0("x", 1:9)
latent <- list(
  visual = x[1:3],
  textual = x[4:6],
  speed = x[7:9]
)

model.cfa <- write_lavaan(latent = latent)
cat(model.cfa)

61 ## #####
62 ## # [-----Latent variables (measurement model)-----]
63 ##
64 ## visual =~ x1 + x2 + x3
65 ## textual =~ x4 + x5 + x6
66 ## speed =~ x7 + x8 + x9
```

67 Should we want to use these latent variables in a full SEM model, we do not need to define
68 the latent variables again, only the new components. In the example below, I add regressions,
69 covariances, and indirect effects to the model. Two of our latent variables (`textual` and `speed`)
70 are now predicted by our mediating variable, `visual`. In turn, `visual` is now predicted by our
71 independent variables, `grade` (the students' grade) and `ageyr` (the students' age, in years).

72 With the `lavaanExtra` syntax, when defining our lists of components, we can think of the
73 `=` sign as "predicted by", a bit like `~` for regression. There is an exception to this for the
74 indirect object, which also allows specifying our variables directly instead. When such is the
75 case, `write_lavaan()` will define all indirect paths automatically.

```
DV <- c("textual", "speed")
M <- "visual"
IV <- c("grade", "ageyr")
```

```

mediation <- list(speed = M, textual = M, visual = IV)
regression <- list(speed = IV, textual = IV)
covariance <- list(speed = "textual", ageyr = "grade", x4 = x[5:6])
indirect <- list(IV = IV, M = M, DV = DV)

model.sem <- write_lavaan(mediation = mediation,
                          regression = regression,
                          covariance = covariance,
                          indirect = indirect,
                          latent = latent,
                          label = TRUE)

cat(model.sem)

76 ## #####
77 ## # [-----Latent variables (measurement model)-----]
78 ##
79 ## visual =~ x1 + x2 + x3
80 ## textual =~ x4 + x5 + x6
81 ## speed =~ x7 + x8 + x9
82 ##
83 ## #####
84 ## # [-----Mediations (named paths)-----]
85 ##
86 ## speed ~ visual_speed*visual
87 ## textual ~ visual_textual*visual
88 ## visual ~ grade_visual*grade + ageyr_visual*ageyr
89 ##
90 ## #####
91 ## # [-----Regressions (Direct effects)-----]
92 ##
93 ## speed ~ grade + ageyr
94 ## textual ~ grade + ageyr
95 ##
96 ## #####
97 ## # [-----Covariances-----]
98 ##
99 ## speed ~~ textual
100 ## ageyr ~~ grade
101 ## x4 ~~ x5 + x6
102 ##
103 ## #####
104 ## # [-----Mediations (indirect effects)-----]
105 ##
106 ## grade_visual_textual := grade_visual * visual_textual
107 ## grade_visual_speed := grade_visual * visual_speed
108 ## ageyr_visual_textual := ageyr_visual * visual_textual
109 ## ageyr_visual_speed := ageyr_visual * visual_speed

```

110 Tables

111 The `nice_fit()` function extracts only some of the most popular fit indices and organize them
 112 such that it is easy to compare models. There is an option to format the table as an APA
 113 flextable (Gohel & Skintzos, 2023), through the `rempsync` package (Thériault, 2023), using
 114 option `nice_table = TRUE`. This flextable object can then be easily exported to Microsoft
 115 Word. Below we fit our two earlier models and feed them to `nice_fit()` as a named list:

```
library(lavaan)
fit.cfa <- cfa(model.cfa, data = HolzingerSwineford1939)
fit.sem <- sem(model.sem, data = HolzingerSwineford1939)

list.mods <- list(`CFA model` = fit.cfa, `SEM model` = fit.sem)
fit_table <- nice_fit(list.mods, nice_table = TRUE)

fit_table
```

Model	χ^2	df	χ^2/df	p	CFI	TLI	RMSEA [90% CI]	SRMR	AIC	BIC
CFA model	85.31	24	3.55	< .001	.93	.90	.09 [.07, .11]	.06	7,517.49	7,595.34
SEM model	114.20	34	3.36	< .001	.93	.88	.09 [.07, .11]	.05	8,640.07	8,758.59
Common guidelines*	—	—	< 2 or 3	> .05	≥ .95	≥ .95	< .05 [.00, .08]	≤ .08	Smaller	Smaller

116 *Based on Schreiber (2017), Table 3.

117 The table can then be saved to word simply using `flextable::save_as_docx()` on the resulting
118 `flextable` object.

```
flextable::save_as_docx(fit_table, path = "fit_table.docx")
```

119 It will also render to PDF in an `rmarkdown` document with output: `pdf_document`, but using
120 `latex_engine: xelatex` is necessary when including Unicode symbols in tables like with the
121 `nice_fit()` function.

122 It is similarly possible to prepare APA tables in Word or other formats with the regression coef-
123 ficients (`lavaan_reg()`), covariances (`lavaan_cov()`), correlations (`lavaan_cor()`), variances
124 (`lavaan_var()`), or user-defined parameters like for indirect effects (`lavaan_defined()`). For
125 example, for indirect effects:

```
lavaan_defined(fit.sem, lhs_name = "Indirect Effect", nice_table = TRUE)
```

Indirect Effect	Paths	SE	Z	p	b	95% CI (b)	b*	95% CI (b*)
grade → visual → textual	grade_visual*visual_textual	0.08	3.35	.001***	0.28	[0.11, 0.44]	0.13	[0.05, 0.20]
grade → visual → textual	grade_visual*visual_speed	0.06	3.05	.002**	0.17	[0.06, 0.28]	0.13	[0.05, 0.21]
grade → visual → textual	ageyr_visual*visual_textual	0.03	-2.47	.014*	-0.08	[-0.15, -0.02]	-0.08	[-0.14, -0.02]
grade → visual → textual	ageyr_visual*visual_speed	0.02	-2.34	.019*	-0.05	[-0.10, -0.01]	-0.08	[-0.15, -0.02]



126

127 Figures

128 There are several packages designed to plot SEM models, but few that people consider satisfying
129 or sufficiently good for publication by default. There are two packages that stand out however,
130 `lavaanPlot` (Lishinski, 2021) and `tidySEM` (van Lissa, 2023b). Yet, even for those excellent
131 packages, most people do not view them as publication-ready or at least optimized in the best
132 possible way.

133 This is what `nice_lavaanPlot` and `nice_tidySEM` aim to correct. Let's compare the default
134 `lavaanPlot()` and `nice_lavaanPlot()` outputs side-by-side for demonstration purposes.

```
lavaanPlot::lavaanPlot(model = fit.sem)
```



137 For reference, nice_lavaanPlot() is a simple wrapper around lavaanPlot::lavaanPlot() and
138 an identical figure can be obtained using only lavaanPlot with the following code:

```
lavaanPlot::lavaanPlot(
  model = fit.sem,
  node_options = list(shape = "box", fontname = "Helvetica"),
  coefs = TRUE,
  stand = TRUE,
  stars = c("regress", "latent", "covs"),
  graph_options = c(rankdir = "LR"),
  sig = .05
)
```


139 As these figures demonstrate, nice_lavaanPlot() has several elements frequently requested

140 by researchers (especially in psychology): (a) a horizontal, rather than vertical, layout; (b) the
 141 coefficients appear by default (but only significant ones); (c) significance stars; and (d) the
 142 use of a sans serif font (as required by APA style for figures).

143 Even so, nice_lavaanPlot is not perfectly optimal for publication, for example for the use
 144 of curved lines, which many researchers dislike. Nonetheless, it will still yield excellent and
 145 satisfying results for a quick and easy check.

146 The best option for publication then is nice_tidySEM. Let's first look at the default output of
 147 the base tidySEM::graph_sem() for reference.

```
tidySEM::graph_sem(fit.sem)
```




149 The author of the tidySEM package notes that

150 This uses a default layout, provided by the igraph package. However, the node
 151 placement is not very aesthetically pleasing. One of the areas where tidySEM
 152 really excels is customization. (van Lissa, 2023a)

153 In this sense, most of the time, both tidySEM and nice_tidySEM will need a layout in order to
 154 yield the best result. One of the benefits of nice_tidySEM is that when our model is simply
 155 made of three "levels": independent variables, mediators, and dependent variables (e.g., for
 156 a path analysis, or if we do not want to draw the items for a full SEM), it is possible to
 157 automatically specify a proper layout by simply feeding it the indirect object that we created
 158 earlier.

```
nice_tidySEM(fit.sem, layout = indirect)
```



160 For reference, below I provide the code necessary to reproduce this figure using the tidySEM
 161 package only.

```
library(tidySEM)


mylayout <- data.frame(
  IV = c("grade", "ageyr"),
  M = c("", "visual"),
  DV = c("textual", "speed")
)
p <- prepare_graph(fit.sem, layout = mylayout)
p <- hide_var(p)
x <- p$edges$est_sig_std
x <- sub("^0", "", x)
x <- sub("^-0", "-", x)
p$edges$label <- x
p$edges$linetype <- 1
p$edges$arrow <- ifelse(p$edges$arrow == "none", "both", p$edges$arrow)
plot(p)
```

162 For the time being, nice_tidySEM only supports this three-level automatic layout, but designs
 163 with more levels are in the works. In the meantime, when the model is more complex (or that
 164 we want to include items), it is necessary to specify the layout manually using a matrix or data
 165 frame, which allows fine-grained control over the generated figure.

```
mylayout <- data.frame(
  IV = c("x1", "grade", "", "ageyr", ""),
  M = c("x2", "", "visual", "", ""),
  DV = c("x3", "textual", "", "speed", "x9"),
  DV.items = c(paste0("x", 4:8))
)
as.matrix(mylayout)
```

	IV	M	DV	DV.items
## [1,]	"x1"	"x2"	"x3"	"x4"
## [2,]	"grade"	" "	"textual"	"x5"
## [3,]	" "	"visual"	" "	"x6"
## [4,]	"ageyr"	" "	"speed"	"x7"
## [5,]	" "	" "	"x9"	"x8"


```
nice_tidySEM(fit.sem, layout = mylayout, label_location = 0.70)
```



172

173 If the figure is still not sufficiently satisfying, it is possible to store the output as a `tidy_sem`
 174 object (by using `plot = FALSE`), which can then be modified according to regular `tidySEM`
 175 syntax. This can be useful to fine-tune and finalize the figure.

```
x <- nice_tidySEM(fit.sem, layout = mylayout, label_location = 0.65,
  reduce_items = c(x = 0.4, y = 0.2), plot = FALSE)
from <- x$edges$from
to <- x$edges$to
x$edges[from == "grade" & to == "speed", "curvature"] <- 40
x$edges[from == "ageyr" & to == "textual", "curvature"] <- -40
plot(x)
```



176

177 The resulting figure can be saved using `ggplot2::ggsave()` (Wickham, 2016):

```
ggplot2::ggsave("my_semPlot.pdf", width = 8, height = 6)
```

178 For reference, below I provide the code necessary to reproduce this figure using the `tidySEM`
179 package only.

```
library(tidySEM)

p <- prepare_graph(fit.sem, layout = mylayout)
p <- edit_graph(p, { label_location <- 0.65 })
p <- hide_var(p)
x <- p$edges$est_sig_std
x <- sub("^0", "", x)
x <- sub("^-0", "-", x)
p$edges$label <- x
items <- p$edges[p$edges$op == "~", "rhs"]
i <- p$nodes$name %in% items
p$nodes[i, ]$node_xmin <- p$nodes[i, ]$node_xmin + 0.4
p$nodes[i, ]$node_xmax <- p$nodes[i, ]$node_xmax - 0.4
p$nodes[i, ]$node_ymin <- p$nodes[i, ]$node_ymin + 0.2
p$nodes[i, ]$node_ymax <- p$nodes[i, ]$node_ymax - 0.2
p$edges$linetype <- 1
p$edges$arrow <- ifelse(p$edges$arrow == "none", "both", p$edges$arrow)
from <- p$edges$from
to <- p$edges$to
p$edges[from == "grade" & to == "speed", "curvature"] <- 40
p$edges[from == "ageyr" & to == "textual", "curvature"] <- -40
plot(p)
```

180 Other differences between `tidySEM` and `nice_tidySEM()` are that: (a) the latter displays
181 standardized coefficients by default (but unstandardized coefficients can be specified with
182 `est_std = FALSE`), (b) if using standardized coefficients, the leading zero is omitted (as
183 preferred by many researchers); (c) does not plot the variances by default, (d) uses full
184 double-headed arrows instead of dashed lines with no arrows for covariances, (e) has further
185 arguments for easy customization (e.g., `reduce_items`), and (f) allows defining an automatic
186 layout in specific cases (as described earlier).

187 Finally, the base function, `tidySEM::graph_sem()`, is difficult to customize in depth. For
188 the aesthetics of `nice_tidySEM()`, for example, we need to rely instead on the `tidySEM`'s
189 `prepare_graph()`, `edit_graph()`, and numerous conditional formatting functions. In contrast
190 to `nice_tidySEM()`, these `tidySEM` functions act more like a grammar of SEM plotting, akin
191 to the popular grammar of graphics, `ggplot2` (Wickham, 2016). This provides great flexibility,
192 but for the occasional user, also comes with an additional burden, as users may for example
193 need to skim through almost 400 undocumented functions, should they want to conditionally
194 edit the resulting `tidy_sem` object.

195 Availability

196 The `lavaanExtra` package is licensed under the MIT License. It is available on CRAN, and
197 can be installed using `install.packages("lavaanExtra")`. The full tutorial website can be
198 accessed at: <https://lavaanExtra.remi-theriault.com/>. All code is open-source and hosted on
199 GitHub, and bugs can be reported at <https://github.com/rempsyc/lavaanExtra/issues/>.

200 **Acknowledgements**

201 I would like to thank Hugues Leduc, Jany St-Cyr, Andreea Gavrila, Patrick Coulombe, Jay
202 Olson, Charles-Étienne Lavoie, and Björn Büdenbender for statistical or technical advice that
203 helped inform some functions of this package and/or useful feedback on this manuscript. I
204 would also like to acknowledge funding from the Social Sciences and Humanities Research
205 Council of Canada.

206 **References**

- 207 Gohel, D., & Skintzos, P. (2023). *flextable: Functions for tabular reporting*. <https://CRAN.R-project.org/package=flextable>
- 208
- 209 Holzinger, K. J., & Swineford, F. (1939). A study in factor analysis: The stability of a bi-factor
210 solution. *Supplementary Educational Monographs*.
- 211 Lishinski, A. (2021). *lavaanPlot: Path diagrams for 'lavaan' models via 'DiagrammeR'*.
212 <https://CRAN.R-project.org/package=lavaanPlot>
- 213 Rosseel, Y. (2012). lavaan: An R package for structural equation modeling. *Journal of*
214 *Statistical Software*, 48(2), 1–36. <https://doi.org/10.18637/jss.v048.i02>
- 215 Thériault, R. (2023). remsync: Convenience functions for psychology. *Journal of Open Source*
216 *Software*, 8(87), 5466. <https://doi.org/10.21105/joss.05466>
- 217 van Lissa, C. J. (2023a). *Plotting graphs for structural equation models*. https://cjvanlissa.github.io/tidySEM/articles/Plotting_graphs.html
- 218
- 219 van Lissa, C. J. (2023b). *tidySEM: Tidy structural equation modeling*. <https://CRAN.R-project.org/package=tidySEM>
- 220
- 221 Wickham, H. (2016). *ggplot2: Elegant graphics for data analysis*. Springer-Verlag New York.
222 <https://ggplot2.tidyverse.org>